

THREE-PHASE-ASYNCHRONOUS-MOTOR 315 MB 4 /PHE

IE3OG31MB401

General data

Type of motor	3~
Type designation	
Frame size	315
Mounting	B3
Frame execution	M
Frame material	Grauguß
Insulationclass	F/B
Terminal box location	left DE
Terminal box orientation	cable gland to the top side
Weight (kg)	990
Rotation Direction	right /left
Vibration level	A
Balancing method	half key
cooling type	IC411
Executed acc. to	IEC 60034-1
noise level	IEC 60034-9

Influential factors

Duty	S1
Ambient temperature (°C)	-20 up to +40
Height of location (m)	1000

Electrical specification

Power 1 50Hz (kW)	160
Power 1 60Hz (kW)	160
Frequency (Hz)	50/60
Voltage 50Hz (V)	400/690
Voltage 60Hz (V)	460/-
Voltage/Frequency tolerance (not valid for range voltage)	+/-10%
Connection	Δ/Y
Poles	4
Efficiency 100% 50Hz (%)	95,8
Efficiency 75% 50Hz (%)	96,0
Efficiency 50% 50Hz (%)	95,9
Efficiency 100% 60Hz (%)	96,2
Efficiency 75% 60Hz (%)	96,4
Efficiency 50% 60Hz (%)	96,3
Power factor	0,87
Starting current factor	7,8
Starting torque factor	2,7
Tilting moment factor	3,3
Rated current 50Hz (A)	276,00/160,00
Rated current 60Hz (A)	239,00/0,00
Eff.Cl.50Hz	IE3

Electrical specification

Eff.Cl.60Hz	IE3
-------------	-----

Mechanical data

Torque (Nm)	1025,67/853,77
Rotation speed (1/min)	1490/1790
Bearing DE	NU319.C3
Bearing NDE	6319.C3
Mounting of bearing DE	loose bearing
Mounting of bearing NDE	fixed bearing
Bearing lifetime	20000
Moment of inertia	4,06

Motor properties

Color	RAL7030
Paint surface	shiny
Protection class	IP55
Cable gland size (cable connection)	2xM63x1,5
Cable gland size (option)	M20x1,5
Cable gland type	Standard
Shaft end	80 x 170
Shaft material	C45
Specification NDE	Plastic fan

Additional option

Protection winding	PTC 150°C
Regreasing device	AS+BS
Condensate draining hole	✓
Condensate draining hole sealing screw	✓