

THREE-PHASE-ASYNCHRONOUS-MOTOR FCPA 100 LA 6 /PHE

IE3AC10LA604N

General data

Type of motor	3~
Type designation	FCPA
Frame size	100
Mounting	B34a
Frame execution	L
Frame material	Aluminium
Insulationclass	F/B
Terminal box location	top DE
Terminal box orientation	cable gland to the right side
Weight (kg)	25.5
Rotation Direction	right /left
Vibration level	A
Balancing method	half key
cooling type	IC411
Executed acc. to	IEC 60034-1
noise level	IEC 60034-9

Influential factors

Duty	S1
Ambient temperature (°C)	-20 up to +40
Height of location (m)	1000

Electrical specification

Power 1 50Hz (kW)	1.5
Power 1 60Hz (kW)	1.5
Frequency (Hz)	50/60
Voltage 50Hz (V)	230/400
Voltage 60Hz (V)	265/460
Voltage/Frequency tolerance (not valid for range voltage)	+/-10%
Connection	Δ/Y
Poles	6
Efficiency 100% 50Hz (%)	82,5
Efficiency 75% 50Hz (%)	82,5
Efficiency 50% 50Hz (%)	80,9
Efficiency 100% 60Hz (%)	88,5
Efficiency 75% 60Hz (%)	88,5
Efficiency 50% 60Hz (%)	86,7
Power factor	0,73
Starting current factor	6
Starting torque factor	2,1
Tilting moment factor	2,1
Rated current 50Hz (A)	6,25/3,59
Rated current 60Hz (A)	5,07/2,94
Eff.Cl.50Hz	IE3

Electrical specification

Eff.Cl.60Hz	IE3
-------------	-----

Mechanical data

Torque (Nm)	15,09/12,59
Rotation speed (1/min)	949/1138
Bearing DE	6206.ZZ.C3
Bearing NDE	6206.ZZ.C3
Mounting of bearing DE	loose bearing
Mounting of bearing NDE	loose bearing
Bearing lifetime	20000
allow. Radial load (X/2)	1287
allow. Radial load (X0)	1425
allow. Radial load (Xmax)	1150
allow. Axial load B3,B5,B35,B14,B34	1125
allow. Axial load V1,V3,V19,V18	1080
Moment of inertia	0,009

Motor properties

Color	RAL7030
Paint surface	shiny
Protection class	IP55
Cable gland size (cable connection)	1xM25x1,5 1xblind plug
Cable gland type	Standard
Shaft end	28 x 60
Shaft material	C45
Specification NDE	Plastic fan
Flange	160


Additional operating points

Voltage operating point 2	265/460
Power operating point 2 (kW)	1.8
Connection operating point 2	Δ/Y
Frequency operating point 2	60
Efficiency class operating point 2	IE2

Dimension drawings

Three-Phase-Asynchronous- Motor FCPA 100 LA 6 /PHE

IE3AC10LA604N



A	AA	AB	AC	AD	AG	B	BB	C	D	E	H	HD	HA	K	L	LM	LB	LD	LL	M	N	P	S	T
160	40	196	191	152	109	140	172	63	28	60	100	252	11	12x16	374	404	314	144	109	130	110	160	M8	3,5
F	8	DH		ED	GD	EB		AB		M10x22		50		7		5		8						