

## THREE-PHASE-ASYNCHRONOUS-MOTOR FCA 71 B 8 /HE

IE2AC07B8011

### General data

|                          |                               |
|--------------------------|-------------------------------|
| Type of motor            | 3~                            |
| Type designation         | FCA                           |
| Frame size               | 71                            |
| Mounting                 | B5                            |
| Frame material           | Aluminium                     |
| Insulationclass          | F/B                           |
| Terminal box location    | top DE                        |
| Terminal box orientation | cable gland to the right side |
| Weight (kg)              | 9.3                           |
| Rotation Direction       | right /left                   |
| Vibration level          | A                             |
| Balancing method         | half key                      |
| cooling type             | IC411                         |
| Executed acc. to         | IEC 60034-1                   |
| noise level              | IEC 60034-9                   |

### Influential factors

|                          |               |
|--------------------------|---------------|
| Duty                     | S1            |
| Ambient temperature (°C) | -20 up to +40 |
| Height of location (m)   | 1000          |

### Electrical specification

|                                                           |           |
|-----------------------------------------------------------|-----------|
| Power 1 50Hz (kW)                                         | 0.12      |
| Power 1 60Hz (kW)                                         | 0.12      |
| Frequency (Hz)                                            | 50/60     |
| Voltage 50Hz (V)                                          | 230/400   |
| Voltage 60Hz (V)                                          | 265/460   |
| Voltage/Frequency tolerance (not valid for range voltage) | +/-10%    |
| Connection                                                | Δ/Y       |
| Poles                                                     | 8         |
| Efficiency 100% 50Hz (%)                                  | 39,8      |
| Efficiency 75% 50Hz (%)                                   | 39,8      |
| Efficiency 50% 50Hz (%)                                   | 39        |
| Efficiency 100% 60Hz (%)                                  | 40        |
| Efficiency 75% 60Hz (%)                                   | 39,8      |
| Efficiency 50% 60Hz (%)                                   | 39        |
| Power factor                                              | 0,57      |
| Starting current factor                                   | 2,8       |
| Starting torque factor                                    | 1,8       |
| Tilting moment factor                                     | 1,9       |
| Rated current 50Hz (A)                                    | 1,33/0,76 |
| Rated current 60Hz (A)                                    | 1,15/0,67 |
| Eff.Cl.50Hz                                               | IE2       |
| Eff.Cl.60Hz                                               | IE2       |


### Mechanical data

|                                     |               |
|-------------------------------------|---------------|
| Torque (Nm)                         | 1,89/1,89     |
| Rotation speed (1/min)              | 605/726       |
| Bearing DE                          | 6202.ZZ.C3    |
| Bearing NDE                         | 6202.ZZ.C3    |
| Mounting of bearing DE              | loose bearing |
| Mounting of bearing NDE             | loose bearing |
| Bearing lifetime                    | 20000         |
| allow. Radial load (X/2)            | 487,5         |
| allow. Radial load (X0)             | 525           |
| allow. Radial load (Xmax)           | 450           |
| allow. Axial load B3,B5,B35,B14,B34 | 475           |
| allow. Axial load V1,V3,V19,V18     | 450           |

### Motor properties

|                                     |                        |
|-------------------------------------|------------------------|
| Color                               | RAL7030                |
| Paint surface                       | shiny                  |
| Protection class                    | IP55                   |
| Cable gland size (cable connection) | 1xM20x1,5 1xblind plug |
| Cable gland type                    | Standard               |
| Shaft end                           | 14 x 30                |
| Shaft material                      | C45                    |
| Specification NDE                   | Plastic fan            |
| Flange                              | 160                    |

**ac motore**



| AC  | AD  | AG  | D  | E  | HD  | L   | LM  | LA | LB  | LL  | M   | N   | P   | S    | T   | F | G  | DH    | EB | ED  | GD |
|-----|-----|-----|----|----|-----|-----|-----|----|-----|-----|-----|-----|-----|------|-----|---|----|-------|----|-----|----|
| 136 | 109 | 101 | 14 | 30 | 189 | 245 | 275 | 10 | 215 | 101 | 130 | 110 | 160 | 4x10 | 3,5 | 5 | 11 | M5x12 | 25 | 2,5 | 5  |