

THREE-PHASE-ASYNCHRONOUS-MOTOR FCA 112 MD 6 /PHE

IE3AC11MD601

General data

Type of motor	3~ progressiv
Type designation	FCA
Frame size	112
Mounting	B5
Frame execution	M
Frame material	Aluminium
Insulationclass	F/B
Terminal box location	top DE
Terminal box orientation	cable gland to the right side
Weight (kg)	54.1
Rotation Direction	right /left
Vibration level	A
Balancing method	half key
cooling type	IC411
Executed acc. to	IEC 60034-1
noise level	IEC 60034-9

Influential factors

Duty	S1
Ambient temperature (°C)	-20 up to +40
Height of location (m)	1000

Electrical specification

Power 1 50Hz (kW)	4
Power 1 60Hz (kW)	4
Frequency (Hz)	50/60
Voltage 50Hz (V)	400/690
Voltage 60Hz (V)	460/795
Voltage/Frequency tolerance (not valid for range voltage)	+/-10%
Connection	Δ/Y
Poles	6
Efficiency 100% 50Hz (%)	86,8
Efficiency 75% 50Hz (%)	86,8
Efficiency 50% 50Hz (%)	85,1
Efficiency 100% 60Hz (%)	91,0
Power factor	0,71
Starting current factor	6,8
Starting torque factor	2
Tilting moment factor	2,1
Rated current 50Hz (A)	9,37/5,43
Rated current 60Hz (A)	7,71/4,47
Eff.Cl.50Hz	IE3
Eff.Cl.60Hz	IE3

Mechanical data

Torque (Nm)	39,59/32,99
Rotation speed (1/min)	965/1158
Bearing DE	6306.ZZ.C3
Bearing NDE	6306.ZZ.C3
Mounting of bearing DE	loose bearing
Mounting of bearing NDE	loose bearing
Bearing lifetime	20000
allow. Radial load (X/2)	1262
allow. Radial load (X0)	1400
allow. Radial load (Xmax)	1125
allow. Axial load B3,B5,B35,B14,B34	1125
allow. Axial load V1,V3,V19,V18	1080
Moment of inertia	0,025

Motor properties

Color	RAL7030
Paint surface	shiny
Protection class	IP55
Cable gland size (cable connection)	1xM32x1,5 1xblind plug
Cable gland type	Standard
Shaft end	28 x 60
Shaft material	C45
Specification NDE	Plastic fan
Flange	250


Additional operating points

Voltage operating point 2	460/795
Power operating point 2 (kW)	4.8
Connection operating point 2	Δ/Y
Frequency operating point 2	60
Efficiency class operating point 2	IE2

Dimension drawings

Three-Phase-Asynchronous- Motor FCA 112 MD 6 /PHE

IE3AC11MD601



AC	AD	AG	D	E	HD	L	LM	LA	LB	LD	LL	M	N	P	S	T	F	G	DH	EB	ED	GD
219	166	117,5	28	60	291	395	435	14	335	151	117,5	215	180	250	4x14,5	4	8	24	M10x22	50	5	7