

THREE-PHASE-ASYNCHRONOUS-MOTOR FCPA 63 B 6 /HE

IE2AC06B6011

General data

Type of motor	3~
Type designation	FCPA
Frame size	63
Mounting	B34a
Frame material	Aluminium
Insulationclass	F/B
Terminal box location	top DE
Terminal box orientation	cable gland to the right side
Weight (kg)	5.5
Rotation Direction	right /left
Vibration level	A
Balancing method	half key
cooling type	IC411
Executed acc. to	IEC 60034-1
noise level	IEC 60034-9

Influential factors

Duty	S1
Ambient temperature (°C)	-20 up to +40
Height of location (m)	1000

Electrical specification

Power 1 50Hz (kW)	0.12
Power 1 60Hz (kW)	0.12
Frequency (Hz)	50/60
Voltage 50Hz (V)	230/400
Voltage 60Hz (V)	265/460
Voltage/Frequency tolerance (not valid for range voltage)	+/-10%
Connection	Δ/Y
Poles	6
Efficiency 100% 50Hz (%)	50,6
Efficiency 75% 50Hz (%)	50,6
Efficiency 50% 50Hz (%)	49,6
Efficiency 100% 60Hz (%)	50,5
Efficiency 75% 60Hz (%)	50,6
Efficiency 50% 60Hz (%)	49,6
Power factor	0,6
Starting current factor	4,4
Starting torque factor	2
Tilting moment factor	2,1
Rated current 50Hz (A)	0,99/0,57
Rated current 60Hz (A)	0,87/0,50
Eff.Cl.50Hz	IE2
Eff.Cl.60Hz	IE2


Mechanical data

Torque (Nm)	1,35/1,12
Rotation speed (1/min)	850/1020
Bearing DE	6201.ZZ.C3
Bearing NDE	6201.ZZ.C3
Mounting of bearing DE	loose bearing
Mounting of bearing NDE	loose bearing
Bearing lifetime	20000
allow. Radial load (X/2)	375
allow. Radial load (X0)	400
allow. Radial load (Xmax)	350
allow. Axial load B3,B5,B35,B14,B34	350
allow. Axial load V1,V3,V19,V18	335

Motor properties

Color	RAL7030
Paint surface	shiny
Protection class	IP55
Cable gland size (cable connection)	1xM20x1,5 1xblind plug
Cable gland type	Standard
Shaft end	11 x 23
Shaft material	C45
Specification NDE	Plastic fan
Flange	90

ac motore



A	100	AA	24	AB	123	AC	120	AD	102	AG	101	B	80	BB	100	C	40	D	11	E	23	H	63	HA	7	K	7x9,5	L	217	LM	247	LA	10	LB	194	LL	101	M	75	N	60	P	90	S	4xM5	T	3	F	4
G	8,5	DH	M4x12	EB	16	ED	3,5	GD	4																																								