

THREE-PHASE-ASYNCHRONOUS-MOTOR FCPA 63 C 2

IE2AC06C2050

General data

Type of motor	3~ progressiv
Type designation	FCPA
Frame size	63
Mounting	B35
Frame material	Aluminium
Insulationclass	F/B
Terminal box location	top DE
Terminal box orientation	cable gland to the right side
Weight (kg)	5.5
Rotation Direction	right /left
Vibration level	A
Balancing method	half key
cooling type	IC411
Executed acc. to	IEC 60034-1
noise level	IEC 60034-9

Influential factors

Duty	S1
Ambient temperature (°C)	-20 up to +40
Height of location (m)	1000

Electrical specification

Power 1 50Hz (kW)	0.37
Power 1 60Hz (kW)	0.44
Frequency (Hz)	50/60
Voltage 50Hz (V)	230/400
Voltage 60Hz (V)	265/460
Voltage/Frequency tolerance (not valid for range voltage)	+/-10%
Connection	Δ/Y
Poles	2
Efficiency 100% 50Hz (%)	69,5
Efficiency 100% 60Hz (%)	72,0
Power factor	0,8
Starting current factor	6,1
Starting torque factor	2,2
Tilting moment factor	2,3
Rated current 50Hz (A)	1,67/0,97
Rated current 60Hz (A)	1,68/0,98
Eff.Cl.50Hz	IE2
Eff.Cl.60Hz	IE2

Mechanical data

Rotation speed (1/min)	2800/3360
Bearing DE	6201.ZZ.C3


Mechanical data

Bearing NDE	6201.ZZ.C3
Mounting of bearing DE	loose bearing
Mounting of bearing NDE	loose bearing
Bearing lifetime	20000
allow. Radial load (X/2)	300
allow. Radial load (X0)	325
allow. Radial load (Xmax)	275
allow. Axial load B3,B5,B35,B14,B34	250
allow. Axial load V1,V3,V19,V18	235
Moment of inertia	0,00075

Motor properties

Color	RAL7030
Paint surface	shiny
Protection class	IP55
Cable gland size (cable connection)	1xM20x1,5 1xblind plug
Cable gland type	Standard
Shaft end	11 x 23
Shaft material	C45
Specification NDE	Plastic fan
Flange	140

Three-Phase-Asynchronous-Motor FCPA 63 C 2
IE2AC06C2050

[illegible]