

THREE-PHASE-ASYNCHRONOUS-MOTOR FOA 180 L 4 /PHE

IE3OG18L4006

General data

Type of motor	3~
Type designation	FOA
Frame size	180
Mounting	B5
Frame execution	L
Frame material	Aluminium
Insulationclass	F/B
Terminal box location	top DE
Terminal box orientation	cable gland to the right side
Weight (kg)	152
Rotation Direction	right /left
Vibration level	A
Balancing method	half key
cooling type	IC411
Executed acc. to	IEC 60034-1
noise level	IEC 60034-9

Influential factors

Duty	S1
Ambient temperature (°C)	-20 up to +40
Height of location (m)	1000

Electrical specification

Power 1 50Hz (kW)	22
Power 1 60Hz (kW)	22
Frequency (Hz)	50/60
Voltage 50Hz (V)	400/690
Voltage 60Hz (V)	460/-
Voltage/Frequency tolerance (not valid for range voltage)	+/-10%
Connection	Δ/Y
Poles	4
Efficiency 100% 50Hz (%)	93,0
Efficiency 75% 50Hz (%)	93,9
Efficiency 50% 50Hz (%)	94
Efficiency 100% 60Hz (%)	93,6
Efficiency 75% 60Hz (%)	94,5
Efficiency 50% 60Hz (%)	94,6
Power factor	0,81
Starting current factor	7,2
Starting torque factor	2,6
Tilting moment factor	3,2
Rated current 50Hz (A)	42,20/24,40
Rated current 60Hz (A)	36,40/0,00
Eff.Cl.50Hz	IE3

Electrical specification

Eff.Cl.60Hz	IE3
-------------	-----

Mechanical data

Torque (Nm)	142,95/118,72
Rotation speed (1/min)	1470/1770
Bearing DE	6310.ZZ.C3
Bearing NDE	6210.ZZ.C3
Mounting of bearing DE	loose bearing
Mounting of bearing NDE	fixed bearing
Bearing lifetime	20000
allow. Radial load (X0)	4370
allow. Radial load (Xmax)	3540
Moment of inertia	0,177

Motor properties

Color	RAL7030
Paint surface	shiny
Protection class	IP55
Cable gland size (cable connection)	2xM40x1,5
Cable gland size (option)	M20x1,5
Cable gland type	Standard
Shaft end	48 x 110
Shaft material	C45
Specification NDE	Plastic fan
Flange	350

Additional option

Protection winding	PTC 150°C
Condensate draining hole	✓
Condensate draining hole sealing screw	✓